





pH Selection Guide

		pH 1	pH 2	pH 3	pH 4
					
Applications	Potable Water		✓		✓
	Waste Water			✓	
	Pool / Spa	✓			
	Process		✓		✓
Mounting Options	Single Open Flow Cell	✓	✓		✓
	Dual Open Flow Cell	✓	✓		✓
	Closed Flow Cell	✓	✓		✓
	Autoclean Immersion			✓	✓
	At Line Tee		✓	✓	✓
	Handrail		✓	✓	✓
	Welding Stub		✓	✓	✓
Specifications	Standard Cable Length	6.5 ft. (2m)	9.8 ft. (3m)	19.6 ft. (6m)	19.6 ft. (6m)
	Inbuilt Temperature		✓	✓	✓
	Max. Temperature	176°F (80°C)	176°F (80°C)	176°F (80°C)	212°F (100°C)
	Back / Front Thread		¾" NPT	¾" NPT	¾" BSP
	Automatic Temp. Compensation		✓	✓	✓
	Water Proof Cable (Submersible)			✓	✓

pH

Chemtrac, Inc.
 1555 Oakbrook Drive
 Suite 100
 Norcross, GA 30093
 USA

PH: 770.449.6233
 US: 800.442.8722
 FX: 770.447.0889
www.chemtrac.com

Mounting Options



Single Open Flow Cell



Double Open Flow Cell



Single Closed Flow Cell



At Line Tee



At Line Tee (quick connect)



Welding Stub

Autoclean Options



Autoclean Insertion



Autoflush Fiber



Autoclean Immersion